

Chimney Hoods'

	WALL MOUNTED								
	3CFT-TILE	3CFT-DEEP 90 X 3CFT-DEEP 90 V	3CFT-9 S X	3CFT-9 R V	6CFT-90 V	3CFT-90 V	5CFB-120 X 5CFB-90 X	3CFT-MAYA	5CFT-90 X
GENERAL FEATURES									
Type	Decorative	Decorative	Decorative	Decorative	Decorative	Decorative	Decorative	Decorative	Decorative
Number of motors	1	1	1	1	1	1	1	1	1
Number of speeds	4	4	4	4	3	4	4	4	4
Intensive speeds	•	•	•	•		•	•	•	•
Halogen light	Halogen	Halogen	Halogen	Halogen	Halogen	Halogen	Halogen	Halogen	Halogen
Auto function sensor			•						
Cable network connection	•	•	•	•	•	•	•	•	•
INSTALLATION									
Mounting	Wall-mounted	•	•	•	•	•	•	•	•
	Ceiling-mounted								
	To the furniture								
	To the furniture or the wall								
Minimum range to plate gas (cm)	65	65	65	65	65	65	65	65	65
Minimum range to plate electric (cm)	55	55	55	55	55	55	55	55	55
OPERATING CONTROL									
Control type	Digital	Electronic	Electronic	Electronic	Mechanical	Electronic	Electronic	Electronic	Electronic
Speed setting display	•	•	•	•		•	•	•	•
Automatic disconnection	•	•	•	•			•		
Number of filters	2	1	3	1	1	1	3	3	3
Filter saturation indicator	•	•	•	•		•	•	•	
Anti-return Valvuva	•	•	•	•	•	•	•	•	•
TECHNICAL SPECIFICATIONS									
Total power (W)	290	290	310	310	290	310	215	255	310
Motor power (W)	250	250	270	270	250	270	175	215	270
Voltage / Frequency (V/Hz)	230/50	230/50	230/50	230/50	230/50	230/50	230/50	230/50	230/50
Fume outlet pipe (diameter in mm)	120/150	120/150	120/150	120/150	120/150	120/150	120/150	120/150	120/150
Extraction motor (m³/h)	Speed I	258	300	270		258	238	262	270
	Speed II	383	460	445		374	372	395	445
	Speed III	511	620	605		631	489	511	745
	Intensive	633	820	745			631	631	
	Speed I	45	35	48		50	46	53	48
Noise level (dB(A))	Speed II	52	45	61		58	55	59	61
	Speed III	59	50	68		68	62	65	68
	Intensive	63	56	73			68	68	
ACCESSORIES									
Carbon filter (optional)	Serie	•			•			•	
Pipe extension kit (optional)	•								

