

		EVACUATION				
		8KG	6KG			
		SF-80	SFE-60 T	SFE-60	SE-60 T	SE-60 E
GENERAL CHARACTERISTICS						
Drying capacity (kg.)	Cotton	8	6	6	6	6
	Delicate materials	4	3	3	3	3
Reversing system		•	•	•	•	•
Stainless steel drum		•	•	•	Galvanized	Galvanized
Electronic humidity sensor						
Extractable condensation tray						
Anti-creases continuous cooling cycle (60 mins)		•	•	120	120	120
Light inside the drum						
Fluff filter		•	•	•	•	•
Door open (180°)		•	•			
Large reversible left/right door		•		•	•	•
Drain water hose supplied					•	•
Vent hose supplied		•	•	•	•	•
N. air outlets		3	Rear	3	1	1
PROGRAMMING						
Drying time control programmer (mins)		150	170	130	130	130
Programmes	Ready to iron	•	•	•	•	•
	Delicate	•	•	•	•	•
	Normal	•	•	•	•	•
OPERATION CONTROL						
Keys	Delayed start	8 h				
	Digital display function					
	Time remaining					
	Start / Stop	•		•	•	•
	Programme start (Start)		•	•	•	•
	Delicate and cotton programme	•	•	•	•	•
	Extra time					
	Machine "on" light	•				
Empty water light						
Clean filter light	•					
TECHNICAL DATA						
Energy efficiency class		C	C	C	C	C
Total power (W)		2.900	2.200	2.200	2.200	2.200
Intensity (A)		16	10	10	10	10
Voltage / Frequency (V/Hz)		230/50	230/50	220-240/50	220-240/50	220-240/50
Electrical consumption (kWh)*		4,60	4,00	3,39	3,39	3,39
DIMENSIONS						
Dimensions (mm)	Height	850	850	850	890	890
	Width	595	595	595	665	665
	Depth	590	540	550	585	585