

Induction Hobs'

	VITROCERAMIC	
	INDUCTION	
	5IFT-40 S	1F-3 S

GENERAL FEATURES

	Induction	4	3
	Halogen		
Number of hot-plates	Radiant (High Light)		
	Double 28 cm circular (H. Light) / Double 28 cm (H. Light)		
	Oval (High Light) / Triple Circular 28 cm (H. Light)		
	Double circular (Quick Rapid)		

1 meter power cable	•	•
---------------------	---	---

PROGRAMMABLE

Timer for up to 99 min.	2	
Warning beeper	•	

OPERATING CONTROL

Power display indication	•	•
General On / Off sensor	•	3
Power selection sensor (+/-)	4	3
Sensor for direct access to 8 o'clock position	1 x ring/foyer	

SAFETY

Recipient detection system	•	•
Residual heat pilot lights	4 (display)	
Automatic safety shut-off	•	•
Safety thermostat	•	
Safety lock	•	

TECHNICAL SPECIFICATIONS

Power and dimensions of the hobs (kW/mm)	Front right	2,8/1,8 180	
	Front left	1,6/1,4 145	3,1 210
	Right rear	2,8/1,8 180	
	Left rear	3/2,2 230	2,2 160
	Centre		3,6 280
Total electrical power	7.2	7.2	
Voltage / Frequency (V/Hz) 220-240 / 50	230/50	220-240/50	

DIMENSIONS

Dimensions (mm)	Width	580/590	580/590
	Depth	510/520	509/510
	Height	57	65

(1) The lower value is for hobs with a stainless steel frame, and the higher value for hobs with chamfered or rounded edges.

