

# Modular Hobs'

	MODULAR									
	INDUCTION		VITROCERAMIC		VITRO-GRILL	ELECTRIC	FRYER	BARBECUE	CRYSTAL-GAS	GAS
	2MF-2I S	3MF-2I S	3MFT-2 S	2MF-2V X	2MF-VG X	2MF-2E X	2MF-FR X	2MF-BR X	2MCF-2G X	2MF-W SS
<b>GENERAL FEATURES</b>										
Vitroc ceramic surface	•	•	•	•	•					
Tempered glass cover									•	
Number of hobs	Radiant vitroc ceramic	Induction	Induction	2	2	1				
	Gas								2	1
	Rapid electric rings (red spot)						2			
Triple Crown Burner										•
Energy regulator								•		
Electronic ignition									•	•
Independent cast iron pan guards										
Double cast iron pan guards										
Independent enamelled pan guards								1	2	1
Double enamelled pan guards										
Module joining strip kit (optional)				•	•	•	•	•	•	•
Electric power cord (Length 100 cm)	•	•	•	•	•	•	•	•	•	•
<b>OPERATING CONTROL</b>										
Gas controls									2	1
Electric controls (0-6 positions)				2		2				
Electric controls (0-9 positions)			•							
Electric controls (0-12 positions)	•	•								
Electric hot-plate ON pilot light				•	•	•	•			
<b>SAFETY</b>										
Safety system (thermocouple)										•
Residual heat pilot lights	2 (display)	2 (display)	2 (display)	2						
Safety thermostat	•	•	•					•		
Oil temperature thermostat								•		
Safety lock	•	•	•							
<b>TECHNICAL SPECIFICATIONS</b>										
Power and dimensions of the hobs (kW/mm)	Front right	1.6 / 1.4	2.2 / 160	1.2 / 140	1.2 / 145		1.5 / 145	Capacity	1	3.5
	Front left	145						Min. 2 litres		
	Right rear	3 / 2.2	3.1 / 210	2-0.7 / 180-120	1.7 / 180		2 / 180	Max. 2.7 litres	3	
	Left rear	210								
	Centre									
Total gas power (kW)									4	3.5
Total electrical power (kW)	3.6	3.6	2.9	2.9	1.2	3.5	2.3	2.4		
Voltage / Frequency (V/Hz)	230/50	220-240/50	230/50	230/50	230/50	230/50	230/50	230/50	230/50	230/50
<b>DIMENSIONS</b>										
Dimensions (mm)	Width	288	288	288	288	288	288	288	288	288
	Depth	510	510	510	510	510	510	510	510	510
	Height	57	65	55	40	42	30	155	50	40

