

Multifunction Plus Ovens'

		MULTIFUNCTION PLUS								
		Pyrolytic		Side Opening Door						
		5H-770 X	6H-760 X	5H-200 LX	5H-200 RX	5H-810 X	5H-800 X	6H-196 X 5H-196 X	6H-185 X 5H-185 X	6H-175 X
GENERAL FEATURES										
Programs of backing combined with microwave										
Site opening door										
				L	R					
Usable volume (l)		55	55	51	51	51	51	51	51	51
No. of cooking programs		7	7	8	8	13	9	8	8	6
Ventilated steam outlet		•	•	•	•	Avanssis	•	•	•	•
Hi-Fi controls										
Illuminated retractable control knobs										
Fixed controls										
Inner glass door										
Fixed grill / Folding grill		- / •	- / •	- / •	- / •	- / •	- / •	- / •	- / •	• / -
4-level grill										
Adjustable grill (2 positions)										
"Pizza" function		•	•	•	•	•	•	•	•	•
"Eco" function		•	•	•	•	•	•	•	•	•
"Celeris" function		•	•	•	•	•	•	•	•	•
"Info" function										
Net compatible (optional)										
Bluetooth Technology										
Electric power cord										
Rotisserie										
Interior illumination										
CLEANING										
Special "Pyrolysis" enamel										
Pyrolytic cleaning (Eco/Normal/Super)		•	• / • / -							
Special "Top Slide" enamel										
Catalytic self-cleaning										
Special "Slide" enamel										
Fume and odour catalysing filter										
PROGRAMMABLE										
Electronic start/stop with warning beeper										
		•	Touch	•	•	•	•	•	•	•
Analog start/stop with warning beeper										
Electronic-stop (with warning beeper)										
Minute minder with warning beeper										
OPERATING CONTROL										
Pyrolysis function pilot light										
"Automatic Chef"										
"Cooking Book"										
Display with text in 17 languages										
LCD display (function control, temp. and time)										
Temperature and time control display										
		• / •	- / •	- / •			- / •	- / •	- / •	
Function and temperature selector		• / •	• / •	• / •	• / •	• / •	• / •	• / •	• / •	• / •
General On/Off selector										
Selector + / -										
Temperature thermostat (50° to 250°C)		35a - 275°C	- / •	•	•	35a - 275°C	35a - 275°C	•	•	•
Temperature pre-selection										
"My Recipes"										
Oven ON pilot light indicator										
Thermostat pilot light indicator										
SAFETY										
Safety thermostat										
Function locking: childproof safety lock										
Automatic safety shut-off										
No. door glass panes										
		3	3	3	3	3	3	2	2	2
TECHNICAL SPECIFICATIONS										
Pyrolysis power (kW)										
		2,83	2,83							
Usable power microwave (kW)										
Total power (kW)		3,38	3,38	2,6	2,6	2,6	2,6	2,6	2,6	2,6
High-Power grill / grill (kW)		2,15 / 1,83	2,15 / 1,83	2,6 / 1,4	2,6 / 1,4	2,6 / 1,4	2,6 / 1,4	2,6 / 1,4	2,6 / 1,4	2,6 / 1,4
Power turbo (kW)		2,8	2,80	2,1	2,1	2,1	2,1	2,1	2,1	2,1
High-Power fixed deck / fixed deck (kW)		1,33	1,33	1,5 / 1,0	1,5 / 1,0	1,5 / 1,0	1,5 / 1,0	1,5 / 1,0	- / 1,0	1,5 / 1,0
Voltage / Frequency (V/Hz)										
		230 / 50	220-240 / 50	230 / 50	230 / 50	230 / 50	230 / 50	230 / 50	230 / 50	230 / 50
Current (Amp)										
		16	16	16	16	16	16	16	16	16
Energy classification										
		A	A	A	A	A	A	A	A	A
ACCESSORIES										
Enamelled deep tray										
		1	1	1	1	1	1	1	1	1
Enamelled tray										
		1	1	1	1	1	1	1	1	1
Special aluminium pastry tray										
						1				
Chrome-plated rack / with safety stop										
		1	1	1	1	1	1	1	1	1
100% removable trays										
		1	1	1	1	2	2	1	1	1
Total Acces										
Auto "Impulse" Slide										
			1					1		1
Pull-System										
Interior guides										
		2	2	2	2	2	2	2	2	2
DIMENSIONS										
Interior dimensions (mm)		Width	435	435	420	420	420	420	420	420
		Height	320	320	322	322	322	322	322	322
		Depth	380	380	380	380	380	380	380	380
Exterior dimension (mm)		Width	592	592	592	592	592	592	592	592
		Height	595	595	595	595	595	595	595	595
		Depth	545	545	552	552	552	552	552	552

