

Vitroc ceramic Hobs'

		VITROCERAMIC					
		TOUCH					
		VF-SLIDE78 S	2VFT-750 S	2VFT-700 S	2VFT-330 S 2VFT-330 X	2VFT-400 X	VFI-400 I
GENERAL FEATURES							
Induction							
Halogen							
Number of hot-pates	Radiant (Hight Light)	2	2	2	2		
	Double 28 cm circular (H. Light) / Double 28 cm (H. Light)		1 / 1				
	Oval (High Light) / Triple Circular 28 cm (H. Light)	1 / 1		- / 1	- / 1		
	Double circular (Quick Rapid)						4
1 meter power cable		•	•	•	•	•	•
PROGRAMMABLE							
Timer for up to 99 min.			1	1	1		
Warning beeper			•	•	•		
OPERATING CONTROL							
Power display indication		•	•	•	•	•	
General On / Off sensor		•	•	•	•	•	
Power selection sensor (+/-)		1	1	3	3	4	
Sensor for direct access to 8 o'clock position							
SAFETY							
Recipient detection system							
Residual heat pilot lights		4	4	3	3	4	4
Automatic safety shut-off		•	•	•	•	•	
Safety thermostat							
Safety lock			•	•	•	•	
TECHNICAL SPECIFICATIONS							
Power and dimensions of the hobs (kW/mm)	Front right	1,8 180	1,8 180			1,2 140	1,2 145
	Front left	1,2 145	1,2 145	1,2 140	1,2 140	1,8 175	1,7 180
	Right rear	2,4-1,7 280-210	2,2/1,5 265-170			2,1 206	2,1 210
	Left rear	1,8 180	2,1-0,7 210-120	1,8 175	1,8 175	1,2 140	1,2 145
	Centre			2,7-1,95-1,05 270-210-140	2,7-1,95-1,05 270-210-140		
	Total electrical power	7,5	7,7	5,7	5,7	6,3	6,2
Voltage / Frequency (V/Hz) 220-240 / 50		220-240/50	220-240/50	220-240/50	220-240/50	220-240/50	230/50
DIMENSIONS							
Dimensions (mm)	Width	780	780	700	580/590	580/590	580
	Depth	520	520	520	510/520	510/520	510
	Height	64	64	55	55	55	55

(1) The lower value is for hobs with a stainless steel frame, and the higher value for hobs with chamfered or rounded edges.

