


DISHWASHER - FAGOR
906013110
2LF-013S



01- AESTHETIC		DETAILS
	BUILT-IN / FREE-STANDING	FREE-STANDING
	ON /OFF BUTTONS	ALUMINUM LOOK
02-COLOR		DETAILS
M	WHITE	YES
03-BASKETS		DETAILS
	UPPER BASKET	
	- TELESCOPIC RUNNER	YES
	- HEIGHT-ADJUSTABLE	SUPER-EASY
	- FOLDING CUP SUPPORTS	4 UPPER
	- RELEASES CUTLERY BASKET SUPPORTS	YES
	- WINE GLASS AND CUP SUPPORTS	2 UPPER
	- ESPACE BASKET	NO
	LOWER BASKET	
	- FOLDING SUPPORTS	YES
	- DOUBLE CUTLERY SUPPORT	YES
	- MULTI-POSITION CUTLERY BASKET	NO
04- GENERAL FEATURES		DETAILS
	OPERATING TYPE	ELECTRONIC
M	ELECTRONIC REGENERATION	YES
	THIRD SPRAYER	YES
	TUB MATERIAL	STAINLESS STEEL
M	VARIABLE CONSUMPTION	YES
	INTERIOR LIGHT	NO
	BACK ADJUSTABLE FEET FROM FRONT	NO
05- PROGRAMMING		DETAILS
	NUMBER OF PROGRAMMES	5
	NUMBER OF DIFFERENT WASH TEMPERATURES	4
	PRE-WASH PROGRAMME	YES
	NORMAL PROGRAMME	65°C
	INTENSIVE PROGRAMME	70°C
	ECONOMICAL PROGRAMME	50°C
	QUICK WASH	55°C
	DELICATE WASH PROGRAMME	NO
06 - OPTIONS		DETAILS
	SINGLE BASKET WASHING	NO
M	START DELAY OPTIONS	1-19H
	TIME REDUCTION	YES
	4-IN-1	YES
07- CONTROLS		DETAILS
	SALT LIGHT INDICATOR	LED
	RINSE AID LIGHT INDICATOR	LED
	END OF CYCLE INDICATOR	ACOUSTIC PILOT SIGNAL
	ON/OFF	YES
	START/PAUSE	YES
	IN OPERATION PILOT	YES
	DIGITAL COUNTDOWN INDICATOR	DISPLAY
	4-IN-1	LED
M	INDICATOR DEFERRED PROGRAMMING	DISPLAY
8- SAFETY		DETAILS
	WATER PROTECTION SYSTEM	YES
	ANTI-FLOODING	YES
	AQUA CONTROL	YES
	ANT-WATER RETURN	YES
	LENGTH INLET HOSE (CM)	HOT (1450MM)
	HEATING SAFETY	DOUBLE
9- ENERGY CARD		DETAILS
M	ENERGY EFFICIENCY CLASS	A+
	CLEANING PERFORMANCE	A
	DRYING PERFORMANCE	A
	NOISE LEVEL (DB(A)RE 1 PW)	50
	NUMBER OF PLACE SETTINGS	12
10- TECHNICAL DATA		DETAILS
	VOLTAGE (V)	220-240
	FRQUENCY (HZ)	50
	CONNECTION RATING (W)	2170 W
	CURRENT (A)	10 A
M	WATER CONSUMPTION (l)	13 L
M	ENERGY CONSUMPTION (KWH)	0.96 KWH
M	TOTAL CYCLE TIME OF REFERENCE PROGRAMME (MIN)	170 MIN
M	TOTAL ANNUAL WATER CONSUMPTION (l)	3640 L
M	TOTAL ANNUAL ENERGY CONSUMPTION (KWH)	283 KWH
11- LOGISTIC INFORMATION		DETAILS
	ADJUSTABLE PLINTH	NO
	PANELLATION THICKNESSES FROM 0 TO 4.5 MM	NO
	ADJUSTABLE FEET	MAX. 30
M	DIMENSIONS WITH WORKTOP (H x W x D) (MM)	850 x 595 x 600
	DIMENSIONS WITHOUT WORKTOP (H x W x D) (MM)	820 x 595 x 570
M	DIMENSIONS OF PACKED PRODUCTS (H x W x D) (MM)	870 x 655 x 655
M	GROSS WEIGHT (KG)	48.2
M	NET WEIGHT (KG)	45.2